

# 4 Channel PoE+ Network Video Recorder

MODEL: VIGI NVR1104H-4P



**H.265+**

**4**  
PoE+ Ports

**53w**  
PoE Budget



**Remote Management**  
Dedicated VIGI app



## Smart Detection

Configuration for Better  
Monitoring\*



## Simple HDD Installation

No need to remove the entire shell



## Built-In Speaker

Real-Time Audio Output



## Onvif

Promises Comprehensive  
Compatibility

## Overview

### VIGI Surveillance Solution

The VIGI professional surveillance system by TP-Link is dedicated to protecting the business that you've worked hard to build—whenever, wherever. Our outstanding functions, reliable quality guarantees, and simplified installation work together to ensure your business stays safe and sound.

## Highlight



#### 4-Channel Live View

Ensures a real-time display of every monitored area on one screen and take everything under your control.



#### Simplified Deployment with PoE+

Easily connect and power your PoE camera with one RJ45 cable transmitting both data and power. No power adapter needed.



#### 4K Video Output

Show more details with up to 8MP resolution for one channel and 16MP decoding capacity in total for all channels



#### Easy Management

Seamlessly manage the NVR and connected cameras via the web UI, NVR UI, VIGI app, and VIGI Security Manager. Customize the management systems to suit your specific needs.



#### Practical Playback


Find the target footage easily by date, event types, and tags. Replay with variable playback speeds to quickly review footage.



#### Mass Storage

Stores up to 10 TB of footage from connected cameras to secure your data for quick, convenient access.

# Network Topology



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

For support and warranty, please visit <http://www.tp-link.com/support>

Specifications are subject to change without notice. TP-Link and VIGI are trademarks of TP-Link Corporation Limited. Other brands and product names are trademarks or registered trademarks of their respective holders. Copyright ©2022 TP-Link Corporation Limited. All rights reserved.

<sup>†</sup>PoE budget calculations are based on laboratory testing. Actual PoE power budget is not guaranteed and will vary as a result of client limitations and environmental factors.

<sup>\*</sup>Some features may operate sub-optimally due to compatibility issues. For best performance, we recommend using VIGI NVR with VIGI cameras.

<sup>^</sup>A hard disk drive (not included) must be installed for operation.

\*Product in box may vary in appearance and specifications.

## TP-Link Corporation Limited

Suite 901, New East Ocean Centre, Tsim Sha Tsui, Hong Kong  
[www.tp-link.com](http://www.tp-link.com)

# Specifications

|                    |                               |  |
|--------------------|-------------------------------|--|
| Models             | VIGI NVR1104H-4P              |  |
| Video Input        | IP Video Input                | 4-Channel  |
|                    |                               | Up to 8 MP Resolution  |
| Network            | Incoming Bandwidth            | 80 Mbps  |
|                    | Outgoing Bandwidth            | 60 Mbps  |
| Video Output       | Recording Resolution          | 8MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF  |
|                    | HDMI Output Resolution        | 1 Channel, Resolution: 3840x2160/30Hz, 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1024x768/60Hz, 1280x720/60Hz |
|                    | VGA Output Resolution         | 1 Channel, Resolution: 1920x1080/60Hz, 1680x1050/60Hz, 1440x900/60Hz, 1280x1024/60Hz, 1024x768/60Hz, 1280x720/60Hz                 |
| Decoding           | Decoding Format               | H.265+/H.265/ H.264+/H.264   |
|                    | Live View/Playback Resolution | 8MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF  |
|                    | Synchronous Playback          | 4-Channel  |
|                    | Capability                    | 2-ch @ 8MP, 4-ch @ 4MP   |
| Network Management | Network Protocols             | TCP/IP, DHCP, DNS, NTP, UPnP   |
| Hard Disk          | SATA                          | 1 SATA Interface   |
|                    | Capacity                      | Up to 10 TB  |
| External Interface | Network Interface             | 1, RJ-45 10/100 Mbps Self-Adaptive Ethernet Interface  |
|                    | USB Interface                 | 2 × USB 2.0  |
| General            | Power Supply                  | 53.5V DC/1.31A   |
|                    | PoE Ports                     | Standard: 802.3af/at<br>PoE Ports: Ports 1-4<br>PoE Budget: 53 W   |
|                    | Working Temperature           | -10~55°C   |
|                    | Product Dimensions            | 200.3 × 200.3 × 43 mm  |