

UISP Console



Mechanical

Dimensions	210.4 x 140.2 x 43.7 mm (8.28 x 5.52 x 1.72")
Weight	1.45 kg (3.2 lb)
Enclosure materials	SGCC steel, polycarbonate

Hardware

Networking interface	(8) 10/100/1,000 MbE RJ45 LAN ports (1) 10/100/1,000 MbE RJ45 WAN port (1) 1/10G SFP+ LAN port (1) 1/10G SFP+ WAN port
Management interface	Ethernet In-Band Bluetooth
Processor	Quad-core ARM® Cortex®-A57 at 1.7 GHz
Memory	4 GB DDR4
Onboard flash storage	16 GB eMMC
Onboard storage	128 GB SSD
Card slot	(1) microSD
Power method	(1) External AC/DC adapter (1) Power TransPort DC input 27V DC, 1.5A
Power supply	24V DC, 2.5A power adapter (included)
Supported voltage range	24–28V DC
Max. power consumption	30W
ESD/EMP protection	Air: ± 15kV, contact: ± 8kV
Operating temperature	-10 to 50° C (14 to 122° F)
Operating humidity	5 to 95% non-condensing
Certifications	CE, FCC, IC

LEDs

System	Status
RJ45 data ports	Speed/link/activity
SFP+ data ports	Speed/link/activity

